

REAR TRAILING ARM - FRONT BUSH

INSTALLATION GUIDE

Contents (parts per pack):

PFF80-1210

2 x bushes (2 x A parts & 4 x B parts)

- 2 x metal sleeves
- 1 x grease





Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- all work to be carried out by a licensed technician;
- all safety precautions adhered to;
- wheel alignment to be checked and adjusted as required after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the rear trailing arm from the car.
- 2. Remove the original bush from the arm, clean any rust and burrs from the arm.
- 3. Apply some washing up liquid to the tapered edge of the 80-1210A part, insert the tapered end into the hole in the arm from the radius side and press the bush through the arm.
- 4. Apply some of the supplied grease to the bore of the A part. Insert two 80-1210B parts into the A part, one from each side.
- 5. Apply some of the supplied grease to the bore of the B parts and push the stainless steel sleeve through the bush.
- 6. Refit the arm to the car.





POWERFLEX 🖀 +44 (0) 1895 460033 📾 sales@powerflex.co.uk 📃 www.powerflex.co.uk